




Teknisk info **Oura 100 + 200 + 300**



Kaminmodell	Oura 100 vridbar pelare	Oura 200	Oura 300
mm	A: 194 B: 543 C: 1030 D: 413 H: 1168 / 1181 	A: 194 B: 543 C: 1030 D: 413 H: 1182 	A: 194 B: 543 C: 1030 D: 413 H: 1444 
Från golv till topputgång mm	1123 / 1142	1138	1138
Energiklass	A	A	A
Nominell kW	7	7	7
Prestanda kW	4-10	4-10	4-10
Värmer antal m ²	30-120	30-120	30-120
Vikt kg	119 / 122	127 / 130 / 153 / 134 / 160	162 / 165
Iläggsmängd kg	1,85	1,85	1,85
Brännkammare inv. bredd mm	398,5	398,5	398,5
Avstånd till brännbart material			
Sida kamin mm	600 / 450	600 / 450	600 / 450
Bakom kamin mm	100 / 150	100 / 150	100 / 150
Möbleringsavstånd mm	850 / 1050	850 / 1050	850 / 1050
Verkningsgrad %	80	80	80
Dammätning NS3058 g/kg torrmateriel	2,12	2,12	2,12
Dammätning Mg/Nm ³ 13% O ₂	11	11	11

Varianter och detaljer

Se mer på heta.dk



Topp i täljsten
Sidoglas



Granit



Vridbar pelare



Luftreglering



Täljsten



Ren förbränning